

Material	Stability Towards Carbonates	Oxide Ion Conduction	Wettability	Sintering Temperature
YSZ ($Y_{0.08}Zr_{0.92}O_2$)	High	Low	High	>1400 °C
GCO ($Gd_{0.2}Ce_{0.8}O_2$)	Intermediate	Intermediate	High	>1300 °C
BTM ($Bi_{0.8}Tm_{0.2}O_{1.5}$)	Low	High	Intermediate	950 °C
BPR ($Bi_{0.8}Pr_{0.2}O_{1.5}$)	Low	High	Low	950 °C
BYS ($Bi_{0.8}Y_{0.15}Sm_{0.05}O_{1.5}$)	High	High	Low	950 °C
BYO ($Bi_{0.8}Y_{0.2}O_{1.5}$)	High	High	Low	950 °C
LSGM ($La_{0.8}Sr_{0.2}Ga_{0.8}Mg_{0.2}O_3$)	Unknown	Intermediate	Unknown	>1100 °C
Ba doped $Na_{0.5}Bi_{0.5}TiO_3$ (Ba-BNT)	High	High	High	1100 °C
LAMOX ($La_2Mo_2O_9$)	Unknown	Intermediate	Unknown	1300 °C
$La_{0.5}Na_{0.5}TiO_3$ (LNT)	High	High	High	1500 °C

High Intermediate Low Unknown



Team of MOLCAR project

Warsaw University of Technology



Alex Martsinchyk



Olaf Dybinski



Karol Cwieka



Lukasz Szablowski

Arek Szczesniak

Kamil Futyma

Jakub Skibinski



Katsiaryna Razumkova




Jarek Milewski
Principal Investigator



Nikolai
Helth Gaukås



Christelle
Denonville



Wen Xing

SINTEF, Oslo



Ewa Stefaniak
Project Manager


Fuel Cell Poland Ltd



Arek Sienko



Artur Olszewski



Modular system based on Molten Carbonate Fuel Cells with tailored composite membranes designed for specific flue gas compositions oriented into CCS integration with an industrial power plant NOR/POLNORCCS/MOLCAR/00-17/2020-00